

LEDDriving BASIC P21/5W



Product family datasheet

Technical data

Product description	Product information		General Product Information	Electrical Data	
	Application (Category and Product specific)	Product type (off-road vs. on-road)	Global order reference	Power input	Nominal voltage
LEDriving BASIC $\hat{=}$ P21/5W	Mainly used for signal/ indicator applications	Off-road $\hat{=}$ P21/5W	1357CW	1.44 W	12.0 V

Product description	Nominal wattage	Test voltage	Photometric Data		Physical Attributes & Dimensions
			Nominal luminous flux	Luminous flux tolerance	Diameter
LEDriving BASIC $\hat{=}$ P21/5W	1 W	13.5 V	85/25 lm	\pm 20 %	20.0 mm

Product description	Lifetime Data		Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
	Lifespan B3	Lifespan Tc	Technology	Date of declaration	Primary article identifier
LEDriving BASIC $\hat{=}$ P21/5W	2000 hr	2000 hr	LED	19-08-2024	4052899463295 4052899414518 4052899414495

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC $\hat{=}$ P21/5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	9bf3b981-7442-439c-a86d-e513fc794734 fe6d71fd-c80e-400d-8cc2-14ed29394294 1d480114-7d33-4144-80cc-0d5f7210d25e

Product family datasheet

Download Data

File	
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conform Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

