OSRAM

LEDriving BASIC R5W



Product family datasheet

Technical data

	Product information			General Product Information	Electrical Data	
Product description	Application	n (Category ct specific)	Product type (off- road vs. on-road)	Global order reference	Power input	Nominal voltage
LEDriving BASIC ≜ R5W	Mainly use signal/ ind application	ndicator R5W		12.0 V		
				Photometric Data		Physical Attributes & Dimensions
Product description	Nominal w	attage	Test voltage	Nominal luminous flux	Luminous flux tolerance	Diameter
LEDriving BASIC ≜ R5W	0 W		13.5 V	55 lm	±20 %	19.0 mm
	Lifetime Data		Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	Lifespan B3	Lifespan Tc	Technology	Date of declaration	Primary ar identifier	ticle
LEDriving BASIC	2000 hr	2000 hr	LED	26-08-2024	40528994	63332

Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC ≜ R5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	12c61241-8e84- 49d2-aad6- 61ee9185fc4c a74ed d59-fe84-466f-9e9c- d76036657cbc 4deab 8c0-c089-4d6a-90f4- 3738f5af799e e8c7bd 92-d6cb-4cf2-9e8f- 8360bae74918

Product family datasheet

Download Data

File



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

