OSRAM

NIGHT BREAKER H4-LED

OSRAM's first NIGHT BREAKER H4 LED for motorcycles





Street-Legal1)

The NIGHT BREAKER LED family - OSRAM's first street-legal1) LED retrofit lamps.



Up to 230% more brightness2) & 6000K

See and be seen with OSRAM. Cool white color temperature similar to daylight. For more safety on the road, especially when driving at night



Up to 5 times longer lifetime3)

Vibration resistant, environmentally friendly, and cost-efficient



4 year OSRAM guarantee

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.

Product family datasheet



With the NIGHT BREAKER H4 LED for Motorcycles, OSRAM's first street legal1) H4-LED replacement lamp for Motorcycles is now on the market

With the street-legal 1) NIGHT BREAKER H4-LED you can now upgrade the function of your high- and low beam lights of your motorcycle to state-of-the-art LED technology. These LED replacement lamps are suitable as a replacement for conventional H4 lamps and bases. They offer a modern and bright white light with a color temperature of up to 6000 Kelvin and impress with up to 230% more brightness2), while the glare of other road users falls below the permissible maximum values by up to 50%2). In comparison to standard lamps, such as halogen lamps, these LED retrofit lamps consume up to 55% less energy and convince thanks to the LED technology and the specially developed vibrationresistant design, with up to 5 times longer life time3). You can now replace your motorcycle lamps with OSRAM's revolutionary NIGHT BREAKER LED retrofit lamps and experience trend-setting brightness with road approval1) Additionally, OSRAM offers a dedicated guarantee on all NIGHT BREAKER LED retrofit lamps2)

Product family datasheet

Technical data

| | 2 2) C min On t glar | | 112. l 112. l 6 less a i i a a a t | Product legal ad 1 1) Approved LED light source - on applies to the respective count in which there is approval or to w an equivalent approval applies the vehicle mode and light functio currently listed i compatibility list more details see www.osram.com led | hich and els on the t. For | and Produ | n (Category ict specific) |
|------------------------|-----------------------------|---|---|--|---|--|---|
| al Product nation | min On t glar | imum ECE R cop with 50% e. | 1112. l % less a r i a a a t a | light source - on applies to the respective count in which there is approval or to wan equivalent approval applies the vehicle modand light functio currently listed i compatibility list more details see www.osram.com | ly ries hich and els ins n the t. For | High and l | ow beam |
| nation Lorder | | trical Data | | | | | |
| | | Electrical Data | | | | | |
| Global order reference | | Nominal voltage | | Nominal wattage | | Power nput coleranc | Test voltage |
| DWNB | 12.0 |) V | | 27 W | = | ±15 % | 13.2 V |
| Photo | ometric Data | 1 | | | | | al Attributes & |
| Light LED | | | inous | Color tempera | ature | Diamet | er |
| W Cool | white 1 | .650/1000 lr | m | 6000 K | | 18.5 mi | m |
| | | | | | l | _ifetime D | ata |
| base | Len | gth | ı | Product weight | | • | Lifespan B3 |
| | 87.4 | mm | 8 | 80.00 g | | 2500 hr | 1500 hr |
| | | | Informati | nation according Art. 33 o | | U | |
| | tandards | ds Date of | | f declaration Primary identifie | | | |
| ology S | itariuarus | | | i | identifier | | |
| | Photo Light LED W Cool base | Photometric Data Light color Note LED fill W Cool white base | Photometric Data Light color Nominal lum flux W Cool white 1650/1000 ln base Length 87.4 mm ilities Certificates & standards | Photometric Data Light color Nominal luminous flux W Cool white 1650/1000 lm base Length 87.4 mm ilities Certificates & Environn Informat Regulation | Photometric Data Light color Nominal luminous Color tempera | Photometric Data Light color Nominal luminous Color temperature LED flux Flux Cool white 1650/1000 lm 6000 K Length Product weight Length Regulatory Information according Art. 33 of Environmental & Regulatory (REAC) Regulation (EC) 1907/2006 (REAC) | Photometric Data Light color Nominal luminous Color temperature planet LED flux W Cool white 1650/1000 lm 6000 K 18.5 mm Lifetime D base Length Product weight Lifespan Tc 87.4 mm 80.00 g 2500 hr standards Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) |

In work

NIGHT BREAKER H4 LED

Product family datasheet

Download Data

File



Brochures

LEDriving Retrofits - Exchange overview (EN)



ref_pim_amsp_product360degreeimages NIGHT BREAKER LED H4-LED 64193DWNB-2HFB

Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

Legal advice

- 1) Approved LED light source only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb-led
- 2) Compared to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 50%
- 3) In comparison to traditional Halogen lamps
- 4) For precise conditions please refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

0